

# ROMUS<sup>®</sup>

## "ROMTACK CONTACT ADHESIVE TAPE" Ref. 98215 98220 98235 98230

### TECHNICAL SHEET - GB

#### Skirting contact adhesive tape with polyester scrim



TECHNICAL DATA	
Adhesive carrier	Polyester scrim
Adhesive material	Acrylic
Liner	Silicon paper, brown
Thickness (without liner)	0.44 – 0.46 mm
Peel adhesion	≥ 25 N/25 mm (DIN EN 1939)*
Shear adhesion	500 g/625 mm <sup>2</sup> (DIN EN 1943)*
Processing temperature	+5 °C à +30 °C
Temperature resistance	-20 °C à +80 °C
Condensation water resistance	High
Ageing resistance	High
Plasticizer resistance	High
Shelf life	UV-protected, dry, room temperature (+23 °C)

\* The values are based on the applicable norms regarding the testing of adhesive tapes.

#### PRODUCT DESCRIPTION

This contact adhesive tape is a highly effective adhesive material made from solvent-free and aging resistant polyacrylat with balanced characteristics for adhesive strength and shear strength.

A polyester scrim serves as stabilization system.

REF	ROMTACK SKIRTINGS – STANDARD DIMENSIONS	Qty Rolls / box	Qty ml / box	MOQ in roll number
98210	25 MM X 50 M	72	3600	576
98215	40 MM X 50 M	6	300	6
98220	50 MM X 50 M	6	300	6
98235	70 MM X 50 M	3	150	3
98230	85 MM X 50 M	3	150	3

#### APPLICATION AREA

This product is a double sided, multifunctional contact adhesive tape. It allows optimal fastening of materials between them, wooden and PVC skirting, and other plastics. Due to its high coating weight the multifunctional tape is especially used for bonding on rough fibrous and uneven wall structures. Therefore recesses can be equalized with adhesive compounds.

The information in this document are indicative They cannot engage the ROMUS responsibility The user or prescriber will check the technical data of the product with the real situation. The company reserves the right to modify all parts of the contents without notice.

Architect / Company :

Project :

Mail :

Tel. :

Distributor :

Tel. :

Mail :