

# PLANK XT PRO

## WOOD - PRODUCT DATASHEET 2021



TECHNICAL DATA (EN 13489)		14 mm
Reaction to fire	EN 14342 Table 1 (when applicable) / EN 13501	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Protoco Natura <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>	EN 13696	N/A
Reduction of sound weighted index $\Delta L_W$ in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	$\geq 17$
Thermal insulation value (RT m <sup>2</sup> K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,11
Construction	3-layer with softwood core	

INSTALLATION	
Installation method	Glue down
Installation instruction	Download from <a href="http://www.tarkett.com">www.tarkett.com</a> Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m <sup>2</sup>	

RECOMMENDED ACCESSORIES	
Installation	Installation kit
Aesthetics	Skirting, Transition moulding, Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Refresher
See more alternatives and the complete range of accessories @ <a href="http://www.tarkett.com">www.tarkett.com</a>	

MAINTENANCE
These Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ <a href="http://www.tarkett.com">www.tarkett.com</a>



T&G



# PLANK XT PRO

## WOOD - PRODUCT DATASHEET 2021

### DESIGN

Real wooden floors for special applications.


PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Oak Authentic	41027002	2 000 x 190 x 14	1-strip	Proteco Natura	Brushed	Minibevel	1	0190-0145	3,5	6	2,28	79,8	7,9
Oak Soft Beige	41027003	2 000 x 190 x 14	1-strip	Proteco Natura	Brushed	Minibevel	1	0190-0145	3,5	6	2,28	79,8	7,9
Oak Rustic	41027001	2 000 x 190 x 14	1-strip	Proteco Natura	Brushed	Minibevel	1	0190-0145	3,5	6	2,28	79,8	7,9
Oak Antique	41027004	2 000 x 190 x 14	1-strip	Proteco Natura	Brushed	Minibevel	1	0190-0145	3,5	6	2,28	79,8	7,9

Due to the nature of the material this table shows typical values.

1: Quercus Robur & Quercus Petraea




Oak Authentic



Oak Soft Beige



Oak Rustic



Oak Antique

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or [www.tarkett.com](http://www.tarkett.com).

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit [www.tarkett.com](http://www.tarkett.com)